

REV	CONTENT	CHK	DATE
V0.0	CONTENT	MYZ	21.07.02

Electrical :

- | | | |
|--|---------------|--------------------|
| | UL | IEC |
| 1.Rated Voltage : | 300V | 250V |
| 2.Rated Current : | 15A | 24A |
| 3.Torque Value : | M3, 4.43Lb.in | M3 , 0.5N.m |
| 4.Wire Range: | 22-14AWG | 2.5mm ² |
| 5.Stripping Length : | 7-8mm | |
| 6.Withstanding Voltage : | AC1600V/1Min. | |
| 7.Operating Temperature : | -40°C~+110°C | |
| 8.RoHS Compliance | | |
| 9.Safety Approval : | cULus CE | |
| 10."★" is the key quality control point. | | |

GT25R-B - XXP - X X - 00

- ① Series No. ③ 1 Single Pitch
2 Double Pitch
- ② Poles
02 02Contacts
03 03Contacts
...
24 24Contacts
- ④ Color: 1 Grey
2 Blue
3 Black
4 Green
5 Orange
6 Red
7 Transparent
8 Yellow
9 White

⑤ Customer Request : 00--Standard

1	Housing	XXXXXX	1	PA66	UL94V-0
2	Contact	XXXXXX	N	Brass	Tin Plated
3	Screws	XXXXXX	N	Steel	Ni Plated
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	MYZ	DATE	21.07.02	SIZE	A4 UNITS mm SHEET/OF 1 / 1
CHK.	DATE		SCALE	1:1	
APP.	DATE				
NAME			GT25R-B-XXP-XX-00		
DWGNO.			XXXX		

Golten 宁波冠泰电子有限公司
NINGBO GOLTEN ELECTRONICS CO., LTD.

